

NFP60T

24H Full Color cameras



NFP60T-GCAT200H

NFP60T-JCAT500MB

NFP60T- SCAT800

- IP66 Metal&Plastic Bullet
- 2MP-5MP-8MP available
- 3.6mm Fixed Lens(2.8mm lens optional)
- 2pcs Array Warm light (3500K), up to 25m

Specification			
Model No.	NFP60T-GCAT200H	NFP60T-JCAT500MB	NFP60T- SCAT800
Video Output Mode	AHD/CVI/TVI/CVBS		
Camera			
Image Sensor	1/2.9"COMS Sensor	1/2.5"COMS Sensor	1/2.8"SONY COMS Sensor
Image Resolution	2M:1920*1080	5M:2560*1944	8M:3840*2160
TV System	PAL/NTSC		
Electronic Shutter	Auto		
Minimum Illumination	0.01Lux(F1.2)	0.1Lux(F1.2)	0.01Lux(F1.2)
	B&W: 0LUX		
Lens			
Focus Length	3.6mm/2.8mm optional		
Focus Control	Fixed		
Lens Type	Fixed		
Night Vision			
IR Cut Filter	YES		
Infrared LED	2pcs Array Warm light (3500K)		
Light Distance	Up to 250M		
IR Status	CDS auto control		
Camera Features			
Day/Night	24H Full Color		
OSD Menu	YES		
WDR	DWDR		
UTC	YES		
Noise Reduction	3-DNR		
Coaxial Audio	/		
White Balance	Auto/Manual		
Gain Control	Auto		
General Specification			

Housing	Metal&Plastic, IP66
Bracket	YES
Operation Temperature	(-10°C ~ +60°C) RH95% MAX
Storage Temperature	(-20°C ~ +60°C) RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	167(L)×65(W)×65(H)
Weight	250g

Dimensions(mm)

