





	1080P@30fps 720P@30fps <b>Support CVBS input</b>
Audio Input	1-ch, RCA
Two-way Audio	1-ch, RCA
<b>Network</b>	
Incoming Bandwidth	48Mbps
Outgoing Bandwidth	60Mbps
Remote Users	128
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE
<b>Video/Audio Output</b>	
VGA Output	1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
HDMI Output	1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Audio Output	1-ch, RCA
Synchronous Playback	8-ch
<b>Encoding</b>	
Recording Resolution	5MP Lite/4MP Lite /1080P/720P/4CIF/CIF
Recording Frame Rate	<b>Main stream:</b> 5MP Lite@6fps 4MP Lite@8fps 2MP Lite@15fps 2MP@8fps 720P@15fps <b>Sub stream:</b> D1@30fps(Max)
<b>Hard Disk</b>	
SATA	1 SATA interface
Capacity	Up to 6TB for each HDD
<b>External Interface</b>	
Network Interface	1RJ45 10M/100M self-adaptive Ethernet Interface
USB Interface	Rear panel:2 x USB2.0
<b>General</b>	
Power Supply	12V DC Power Consumption: ≤ 8 W( without HDD )
Working Environment	-10°C ~ + 55°C ( +14°F ~ +131°F ), Humidity ≤ 90% RH(non-condensing)
Dimensions(W×D×H)	255mm ×215mm× 42mm (10.0" × 8.5"×1.7")
Weight ( without HDD )	≤1.1 Kg ( 2.42lb )

## Dimensions



## Rear Panel

Take NT-XVR6104E1 for example

