

NFP60K

Easy Series IP camera



NFP60K-MW530AU

NFP60K-MW350DU

NFP60K- MS880BU

- IP67 full metal Bullet
- H.265+/H.265/H.264+/H.264 Compression Method
- 3MP-5MP-8MP available
- 3.6mm Fixed Lens(2.8mm lens optional)
- 2PCS Array IR LED,up to 25m
- With Internal POE

- 3 image scene modes: transparent, bright, standard, and the image style can be switched at will.
- Dark area perception algorithm : at night, which improves the visibility of objects in the dark part of the image by 50 %, but does not affect the exposure in bright areas .
- Balanced exposure engine : at night. When people and cars approach, balance the exposure of near and far images, the exposure of near faces is better suppressed, and the visible distance of distant scenes is about 5 meters longer than other brands.

| Specification | | | |
|----------------------|---------------------------------|---------------------|----------------------|
| Model No. | NFP60K-MW530AU | NFP60K-MW350DU | NFP60K- MS880BU |
| Camera | | | |
| Image Sensor | 3MP 1/2.7"COMS Sensor | 5mp 1/3"COMS Sensor | 8MP1/2.8"COMS Sensor |
| Image Format | 16:9 | | |
| Compression | H.264/H.264+/H.265/H.265+ | | |
| TV System | PAL/NTSC | | |
| Electronic Shutter | Support automatic / manual mode | | |
| S/N Ratio | ≥ 50 dB | ≥ 50 dB | ≥ 72 dB |
| Video Output | Network | | |
| Scanning System | Progressive | | |
| Reset Button | Optional | | |
| Minimum Illumination | 0.01Lux | 0.01Lux | 0.01Lux |
| Lens | | | |
| Focus Length | 3.6mm/2.8mm optional | | |
| Focus Control | Board | | |
| Lens Type | Board | | |
| Night Vision | | | |
| IR Cut Filter | YES | | |
| Infrared LED | 2PCS Array IR LED | | |
| Light Distance | Up to 25M | | |
| IR Status | AGC auto control | | |

| Network | | | |
|----------------------|---|-------------------------------|----------------------------------|
| Ethernet | One RJ45, 10/100M adaptive Ethernet interface 2KV lightning protection meter | | |
| Audio port | One audio input One audio output, G711U/G711A encoding, support simplex two-way voice intercom | | |
| Protocol | Support HTTP/RTSP/NTP/DHCP/ONVIF/P2P lamp network protocol, optional GB28181, RTMP and multiple private NVR protocols | | |
| ONVIF | support | | |
| P2P | yes | | |
| POE | support | | |
| Video Delay | 0.3S (Within the Lan) | 0.3S (Within the Lan) | 0.5S (Within the Lan) |
| Main Stream 1 | 2304*1296 @25fps | 2880*1620@20fps | 3840*2160@20fps, |
| Main Stream 2 | 1080P/720P/D1@30fps | 2560*1440@20fps | 2592*1944@15fps |
| Main Stream 3 | N/A | 2304*1296@20fps | 2560*1440@20fps, |
| Sub Stream 1 | D1/VGA/640*360/CIF @30fps | D1, 640*360, 2CIF, CIF @20fps | 720P/D1 /640*360 /2CI/ CIF@30fps |
| Sub Stream 2 | N/A | N/A | D1/640*360/2CIF /CIF @30fps |
| Sub Stream 3 | N/A | N/A | N/A |
| IE Brower | IE6.0 , Google Chrome, Firefox | | |
| Smart Phone | IPhone, Android | | |
| AI Function | | | |
| Intelligent Analysis | motion detection based on human detection; report alarm information to the backend or App | | |
| Camera Features | | | |
| Day/Night | Dual filter switcher, AUTO/Color/B&W/EXT | | |
| OSD Menu | YES | | |
| UTC | YES | | |
| BLC | Support | | |
| WDR | DWDR | DWDR | WDR |
| Motion Detection | Support | | |
| Privacy Masking | 4 Zones | | |
| Regional Enhancement | 8 Zones | | |

| | |
|------------------------------|---|
| Noise Reduction | Support 2D,3D noise reduction |
| Recording Mode | NVR/CMS/Web |
| Language | Chinese, English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Italian |
| General Specification | |
| Housing | Metal, IP67 |
| Bracket | YES |
| Operation Temperature | (-10°C ~ +60°C) RH95% MAX |
| Storage Temperature | (-20°C ~ +60°C) RH95% Max |
| Power Source | DC12V±10%, 450mA |
| Dimension | 170(L)×60(W)×60(H) |
| Weight | 450g |

Dimensions(mm)

