

NPT40T

Easy Series IP camera



NPT40-MW350CUAF

NPT40- MS880AUAF

- IP67 full metal Bullet
- H.265+/H.265/H.264+/H.264 Compression Method
- 3MP-5MP-8MP available
- 2.8-12mm Motor Zoom lens
- 4PCS Array IR LED, up to 40m
- With Internal POE
- 3 image scene modes: transparent, bright, standard, and the image style can be switched at will.
- Dark area perception algorithm : at night, which improves the visibility of objects in the dark part of the image by 50 %, but does not affect the exposure in bright areas .
- Balanced exposure engine : at night. When people and cars approach, balance the exposure of near and far images, the exposure of near faces is better suppressed, and the visible distance of distant scenes is about 5 meters longer than other brands.

Specification

Model No.	NPT40-MW350CUAF	NPT40- MS880AUAF
Camera		
Image Sensor	5mp 1/3"COMS Sensor	8MP1/2.8"COMS Sensor
Image Format	16:9	
Compression	H.264/H.264+/H.265/H.265+	
TV System	PAL/NTSC	
Electronic Shutter	Support automatic / manual mode	
S/N Ratio	≥ 50 dB	≥ 72 dB
Video Output	Network	
Scanning System	Progressive	
Reset Button	Optional	
Minimum Illumination	0.01Lux	0.01Lux
Lens		
Focus Length	2.8-12mm Motor Zoom lens	
Focus Control	Auto	
Lens Type	Auto	
Night Vision		
IR Cut Filter	YES	
Infrared LED	4PCS Array IR LED	
Light Distance	Up to 40M	
IR Status	AGC auto control	
Network		
Ethernet	One RJ45, 10/100M adaptive Ethernet interface 2KV lightning protection meter	
Audio port	One audio input One audio output, G711U/G711A encoding, support simplex two-way voice intercom	
Protocol	Support HTTP/RTSP/NTP/DHCP/ONVIF/P2P lamp network protocol, optional GB28181, RTMP and multiple private NVR protocols	

ONVIF	support	
P2P	yes	
POE	support	
Video Delay	0.3S (Within the Lan)	0.5S (Within the Lan)
Main Stream 1	2880*1620@25fps	3840*2160@20fps,
Main Stream 2	2560*1440@25fps	2592*1944@15fps
Main Stream 3	2304*1296@25fps	2560*1440@20fps,
Sub Stream 1	720P,D1(default),640*360,2CIF、CIF @20fps	720P/D1 /640*360 /2CI/ CIF@30fps
Sub Stream 2	D1,640*360,2CIF,CIF(default)@25fps	D1/640*360/2CIF /CIF @30fps
Sub Stream 3	N/A	N/A
IE Brower	IE6.0 , Google Chrome, Firefox	
Smart Phone	IPhone, Android	
AI Function		
Intelligent Analysis	motion detection based on human detection; report alarm information to the backend or App	
Camera Features		
Day/Night	Dual filter switcher, AUTO/Color/B&W/EXT	
OSD Menu	YES	
UTC	YES	
BLC	Support	
WDR	DWDR	WDR
Motion Detection	Support	
Privacy Masking	4 Zones	
Regional Enhancement	8 Zones	
Noise Reduction	Support 2D,3D noise reduction	
Recording Mode	NVR/CMS/Web	
Language	Chinese, English, Bulgarian, Polish, Arabic, German, Russian, French, Korean,Portuguese, Japanese, Turkish, Spanish, Italian	
General Specification		
Housing	Metal, IP67	

Bracket	YES
Operation Temperature	(-10℃ ~ +60℃) RH95% MAX
Storage Temperature	(-20℃ ~ +60℃) RH95% Max
Power Source	DC12V±10%, 450mA
Dimension	255(L)×80(W)×85(H)
Weight	740g

Dimensions(mm)

