

NHL202A

2MP/5MP/8MP 4-in-1 cameras



NHL202A-GCAT200HB

NHL202A-GCAT500EC

NHL202A- SCAT800

- IP 67 Plastic+ metal dome
- 2MP-5MP-8MP available
- 3.6mm Fixed Lens(2.8mm lens optional)
- 2PCS Array LED, up to 20m

Specification			
Model No.	NHL202A-GCAT200HB	NHL202A-GCAT500EC	NHL202A- SCAT800
Video Output Mode	AHD/CVI/TVI/CVBS		
Camera			
Image Sensor	1/2.9"COMS Sensor	1/3"COMS Sensor	1/2.8"SONY COMS Sensor
Image Resolution	2M:1920*1080	5M:2560*1944	8M:3840*2160
TV System	PAL/NTSC		
Electronic Shutter	Auto		
Minimum Illumination	0.01Lux(F1.2)	0.05Lux(F1.2)	0.01Lux(F1.2)
	B&W: 0LUX		
Lens			
Focus Length	3.6mm/2.8mm optional		
Night Vision			
IR Cut Filter	YES		
Infrared LED	2PCS Array IR LED		
Light Distanc	Up to 20M		
Camera Features			
Day/Night	Dual filter switcher, AUTO/Color/B&W/EXT		
OSD Menu	YES		
WDR	DWDR	DWDR	WDR
Noise Reduction	3-DNR	DNR	3-DNR
AWB	GRAY WORLD/ATW/MWB	ATW/MWB	PRO/GRAY WORLD/ATW/MWB
MIRROR / FLIP	CLOSE/OPEN		
UTC	YES		
Gain Control	Auto		
General Specification			
Housing	Plastic+ metal , IP67		
Bracket	YES		
Operation Temperature	(-10℃ ~ +60℃) RH95% MAX		
Storage Temperature	(-20℃ ~ +60℃) RH95% Max		
Power Source	DC12V±10%, 450mA		
Dimension	109(L)×87(W)		
Weight	270g		

Dimensions(mm)