

NIHF2

2MP/5MP/8MP 4-in-1 cameras



NIHF2-GCAT200HB

NIHF2-GCAT500EC

NIHF2- SCAT800

- IP 67 Full metal bullet
- 2MP-5MP-8MP available
- 3.6mm Fixed Lens(2.8mm lens optional)
- 3PCS Array LED, up to 25m

| Specification | | | |
|-----------------------|--|-----------------|------------------------|
| Model No. | NIHF2-GCAT200HB | NIHF2-GCAT500EC | NIHF2- SCAT800 |
| Video Output Mode | AHD/CVI/TVI/CVBS | | |
| Camera | | | |
| Image Sensor | 1/2.9"COMS Sensor | 1/3"COMS Sensor | 1/2.8"SONY COMS Sensor |
| Image Resolution | 2M:1920*1080 | 5M:2560*1944 | 8M:3840*2160 |
| TV System | PAL/NTSC | | |
| Electronic Shutter | Auto | | |
| Minimum Illumination | 0.01Lux(F1.2) | 0.05Lux(F1.2) | 0.01Lux(F1.2) |
| | B&W: 0LUX | | |
| Lens | | | |
| Focus Length | 3.6mm/2.8mm optional | | |
| Night Vision | | | |
| IR Cut Filter | YES | | |
| Infrared LED | 3PCS Array IR LED | | |
| Light Distanc | Up to 25M | | |
| Camera Features | | | |
| Day/Night | Dual filter switcher, AUTO/Color/B&W/EXT | | |
| OSD Menu | YES | | |
| WDR | DWDR | DWDR | WDR |
| Noise Reduction | 3-DNR | DNR | 3-DNR |
| AWB | GRAY WORLD/ATW/MWB | ATW/MWB | PRO/GRAY WORLD/ATW/MWB |
| MIRROR / FLIP | CLOSE/OPEN | | |
| UTC | YES | | |
| Gain Control | Auto | | |
| General Specification | | | |
| Housing | Metal, IP67 | | |
| Bracket | YES | | |
| Operation Temperature | (-10℃ ~ +60℃) RH95% MAX | | |
| Storage Temperature | (-20℃ ~ +60℃) RH95% Max | | |
| Power Source | DC12V±10%, 450mA | | |
| Dimension | 166(L)×63(W)×64(H) | | |
| Weight | 320g | | |

Dimensions(mm)