

NIRBHTAF

2MP/5MP/8MP 4-in-1 cameras



NIRBHTAF -GCAT200HB

NIRBHTAF -GCAT500EC

NIRBHTAF - SCAT800

- IP 67 Full metal bullet
- 2MP-5MP-8MP available
- 2.8-12mm /2.7-13.5mm Motorized lens
- 24PCS SMD LED, up to 40m

Specification			
Model No.	NIRBHTAF-GCAT200HB	NIRBHTAF -GCAT500EC	NIRBHTAF - SCAT800
Video Output Mode	AHD/CVI/TVI/CVBS		
Camera			
Image Sensor	1/2.9"COMS Sensor	1/3"COMS Sensor	1/2.8"SONY COMS Sensor
Image Resolution	2M:1920*1080	5M:2560*1944	8M:3840*2160
TV System	PAL/NTSC		
Electronic Shutter	Auto		
Minimum Illumination	0.01Lux(F1.2)	0.05Lux(F1.2)	0.01Lux(F1.2)
	B&W: 0LUX		
Lens			
Motorized lens	2.8-12mm for 2mp-5mp,2.7-13.5mm for 8mp		
Night Vision			
IR Cut Filter	YES		
Infrared LED	24PCS SMD IR LED		
Light Distanc	Up to 30M		
Camera Features			
Day/Night	Dual filter switcher, AUTO/Color/B&W/EXT		
OSD Menu	YES		
WDR	DWDR	DWDR	WDR
Noise Reduction	3-DNR	DNR	3-DNR
AWB	GRAY WORLD/ATW/MWB	ATW/MWB	PRO/GRAY WORLD/ATW/MWB
MIRROR / FLIP	CLOSE/OPEN		
UTC	YES		
Gain Control	Auto		
General Specification			
Housing	Metal, IP67		
Bracket	YES		
Operation Temperature	(-10°C ~ +60°C) RH95% MAX		
Storage Temperature	(-20°C ~ +60°C) RH95% Max		
Power Source	DC12V±10%, 760mA		
Dimension	145(L)×89(W)		
Weight	720g		

Dimensions(mm)

