

NVDMIR

2MP/5MP 4-in-1 cameras



NVDMIR-GCAT200HB

NVDMIR-GCAT500EC

- IP 67 Full metal bullet
- 2MP-5MP available
- 3.6mm Fixed Lens(2.8mm lens optional)
- 12PCS IR LED, up to 15m

Specification

Specification		
Model No.	NVDMIR-GCAT200HB	NVDMIR-GCAT500EC
Video Output Mode	AHD/CVI/TVI/CVBS	
Camera		
Image Sensor	1/2.9"COMS Sensor	1/3"COMS Sensor
Image Resolution	2M:1920*1080	5M:2560*1944
TV System	PAL/NTSC	
Electronic Shutter	Auto	
Minimum Illumination	0.01Lux(F1.2)	0.05Lux(F1.2)
	B&W: 0LUX	
Lens		
Focus Length	3.6mm/2.8mm optional	
Night Vision		
IR Cut Filter	YES	
Infrared LED	12PCS IR LED	
Light Distanc	Up to 15M	
Camera Features		
Day/Night	Dual filter switcher, AUTO/Color/B&W/EXT	
OSD Menu	YES	
WDR	DWDR	DWDR
Noise Reduction	3-DNR	DNR
AWB	GRAY WORLD/ATW/MWB	ATW/MWB
MIRROR / FLIP	CLOSE/OPEN	
UTC	YES	
Gain Control	Auto	
General Specification		
Housing	Metal, IP67	
Bracket	YES	
Operation Temperature	(-10℃ ~ +60℃) RH95% MAX	
Storage Temperature	(-20℃ ~ +60℃) RH95% Max	
Power Source	DC12V±10%, 450mA	
Dimension	95(L)×65(W)	
Weight	280g	

Dimensions(mm)

