

PS0412EX

4 Port POE/IEEE802.3af/at/100Mbps



Key Features

- IEEE 802.3af/at POE compliant to simplify deployment and installation
- Auto-detection and protection of non-standard POE devices
- IEEE 802.3x flow control protects against lost packets for reliable data transmission
- Simple Plug and Play installation
- switch Extend, 1-4Port V-Lan on; 5E cat Cable Distance 250M;Data Rate 10Mbps
- Total POE power budget: 65W, up to 30W per port
- Compact Design Fits Easily in VLAN Access
- Easy installation and maintenance

Technical Specification

| | | |
|-----------------------------|----------------------------|--|
| Network Switch | Network Standards | IEEE 802.3 10-BASE-T (Ethernet) IEEE 802.3u 100-BASE-TX (Fast Ethernet) IEEE 802.3x Flow Control (full-duplex flow control) IEEE 802.3af Power over Ethernet |
| POE Standard | POE Spec | POE Standard: IEEE 802.3af/at Power over Ethernet / PSE PD classification identity POE over current protection POE circuit sorting protection POE Power Output: Per Port 52V DC, Max. 30 watts (IEEE 802.3af/at) Power Budget: Max. 65W Power Pin Assignment: 1/2(+), 3/6(-) |
| Network port | Filtering/Forwarding Rates | 100Mbps port-148,000pps 10Mbps port-14,880pps |
| | Network Interface | 4 x 10/100Mbps RJ-45 POE 1~4 Ports 2x 10/100Mbps RJ-45 Uplink 5~6 Ports |
| | Extend/ON | 1~4Port 10Mbps POE+Vlan 250M ;5~6Port 10/100Mbps |
| Network connector | Transmission Media | 10 BaseT Cat 3,4,5 UTP/STP 100M BaseTx CAT 5 UTP/STP |
| Power | Power Input | Input: 100~240V/AC, 50~60 Hz, 1A Internal Power Supply |
| | Power Consumption | 65Watts(Max) |
| Size &Weight | Dimensions: (L x W x H) | 185*124*44mm /1kg |
| Environment | Temperature | Operating: -5~45°C Storage: -20~70°C Humidity: 10~90%, Non-condensing |
| | | |
| LED Status Indicator | | Per Port: Link/Act((Green), POE Port:POE in use(Orange) Power:PWR(Orange) |
| Certifications | | CE/FCC |